



## EVOLUTION XT SAE 10W-40

EVOLUTION XT SAE 10W-40 is a high alloyed motor oil which provides fuel economical operation of the motors due to the choice of additives, the base oils and the viscosity grade. To maintain the performance of the SAE 10W class as well as a low volatility EVOLUTION XT SAE 10W-40 contains synthetic base oils which meet the high tech requirements.

EVOLUTION XT SAE 10W-40 is perfectly suited for all-season operation in modern cars with fuel and diesel motors. Excellent motor cleanliness is guaranteed, likewise for turbocharged motors as well as cars with a catalyst.

### Specification

ACEA A3/B4

API SN/CF

### Recommended application

MB-Freigabe 229.1

VW 501 01, 505 00

Technical data	Unit	Test according	EVOLUTION XT SAE 10W-40
density at 15°C	Kg/m <sup>3</sup>	DIN EN ISO 12185	868
Flammable COC	°C	DIN ISO 2592	mind. 220
Pourpoint	°C	DIN ISO 3016	-39
Viscosity 40°C	mm <sup>2</sup> /s	DIN 51562-1	91,9
Viscosity 100°C	mm <sup>2</sup> /s	DIN 51562-1	14,0
VI		DIN ISO 2909	157
TBN	mgKOH/g	DIN ISO 3771	10,2

The expiration date is 2 years after production date under the permission that the product is stored in a dark, dry and cool place.

The given data are typical data. Please observe instructions.



powered by **Quality.**

**PROFI-TECH GmbH** • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen • Germany  
Tel: +49 7541 40286-0 • Fax: +49 7541 40286-99 • [www.profi-tech.com](http://www.profi-tech.com) • [info@profi-tech.com](mailto:info@profi-tech.com)

**PROFI-CAR** is a international registered trademark of **PROFI-TECH GmbH**